

# OPEN TOP CONTAINER

ISO Size Type Code: 22U1

# 20'



- Specially designed for
  - **over-height cargo**
  - **heavy loads**
  - **loading from top side**, e.g. by crane
  - **loading from door side**, e.g. with cargo hanging from overhead tackle
- Floor height 170 mm (ground level to interior floor surface, tolerance deviation possible)
- Door header can be swung out on all open top containers
- If required, we can provide disposable tarpaulins. Using one-way tarpaulins requires that the corner castings be accessible
- For fastening tarpaulins, lashing bars are available on the outside of the walls
- Equipped with forklift pockets for loaded containers
- Numerous lashing devices on the top and bottom longitudinal rails and the corner posts
- Lashing devices have a permissible load of 1,000 kg (2,205 lbs) each
- For dimensions of roof and door openings, please see page 30

8' 6" high	Inside dimensions				Weights			Capacity	Hapag-Lloyd serial number excerpt	
	Length	Width	Height		Max. gross kg lbs	Tare kg lbs	Max. payload kg lbs	m <sup>3</sup> ft <sup>3</sup>		
			Middle mm ft	Side mm ft						
<b>Wooden floor</b> Steel container with corrugated walls and removable tarpaulin	5,895 19' 4 1/8"	2,350 7' 8 1/2"	2,380 7' 9 5/8"	2,340 7' 8 1/8"	32,500 71,650	2,450 5,402	30,050 66,248	32.5 1,148	HLXU	362000–362999
			2,376 7' 9 1/2"	2,346 7' 8 3/8"		2,500 5,512	30,000 66,138	32.7 1,155	HLXU	360000–361999

  

8' 6" high	Inside dimensions				Weights			Capacity	Hapag-Lloyd serial number excerpt	
	Length	Width	Height		Max. gross kg lbs	Tare kg lbs	Max. payload kg lbs	m <sup>3</sup> ft <sup>3</sup>		
			Middle mm ft	Side mm ft						
<b>Steel floor</b> Steel container with corrugated walls and removable tarpaulin	5,895 19' 4 1/8"	2,352 7' 8 1/2"	2,378 7' 9 5/8"	2,344 7' 8 1/4"	32,500 71,650	2,300 5,071	30,200 66,579	32.5 1,148	HLBU	801000–801599
									HLBU	803300–803619

For further information about the steel-floor container, please see page 32.