



- Suitable for **heavy loads and oversized cargo**
- Equipped with fork-lift pockets for loaded containers
- Numerous **very strong lashing devices** on the corner posts, longitudinal rails and on base ends
- Lashing devices have a permissible load up to 5,000 kg (11,023 lbs) each
- Maximum payload can only be used if cargo weight is distributed over the total floor area of Flatrack
- If heavy loads are shorter, the payload is reduced. Please contact your Hapag-Lloyd office for stowage advice
- Flatracks are delivered without stanchions. If stanchions are required, please inform us upon booking
- Flatracks are equipped with spring-assisted collapsible end walls and twistlocks to interlock 7 units into a 8'6" high pile
- Timber-treated according to Australian requirements
- Welding on Flatracks is not allowed

8' 6" high	Inside dimensions					Weights			Hapag-Lloyd serial number excerpt	
	Length between corner posts mm ft	Width between corner posts mm ft	Width over floor/ bottom side rails mm ft	Height floor to top face (inside height) mm ft	Height of bottom mm ft	Max. gross kg lbs	Tare kg lbs	Max. payload kg lbs		
<b>Flat/Platform</b> with flushfolding end walls and softwood floor	5,612 18' 4 <sup>7</sup> / <sub>8</sub> "	2,227 7' 3 <sup>5</sup> / <sub>8</sub> "	2,210 7' 3"	2,219 7' 3 <sup>3</sup> / <sub>8</sub> "	370 1' 2 <sup>1</sup> / <sub>2</sub> "	34,000 74,957	2,740 6,041	31,260 68,916	HLXU	268800–269199
	5,638 18' 6"		2,208 7' 2 <sup>7</sup> / <sub>8</sub> "	2,235 7' 4"		40,000 88,184			2,940 6,482	37,060 81,702
		5,638 18' 6"	2,194 7' 2 <sup>3</sup> / <sub>8</sub> "	2,233 7' 3 <sup>7</sup> / <sub>8</sub> "			45,000 99,207	2,900 6,393		
	5,638 18' 6"									