

GENERAL PURPOSE CONTAINER

ISO Size Type Code: 22G0, 22G1

20'



- Suitable for any general cargo
- **Fork-lift pockets** for loaded containers
- Various **lashing devices with a permissible load** of 1,000 kg (2,205 lbs) each on the top and bottom longitudinal rails and the corner posts
- Lashing rings on each top longitudinal rail, particularly suitable for the transport of **hanging garment** equipment
- Majority of containers tested and certified for ONE-DOOR-OFF OPERATION, but then with limited stack weight
- Containers may be equipped with **liner bags** suitable for bulk cargo, e.g. malt
- **Floor height** 170 mm (ground level to interior floor surface, tolerance deviation possible)

8' 6" high	Inside dimensions			Door openings		Weights			Capacity
	Length	Width	Height	Width	Height	Max. gross	Tare	Max. payload	
	mm ft	mm ft	mm ft	mm ft	mm ft	kg lbs	kg lbs	kg lbs	m ³ ft ³
Wooden floor Steel container with corrugated walls	5,900	2,352	2,393	2,340	2,292	32,500	2,300	30,200	33.2
	19' 4¼"	7' 8⅝"	7' 10¼"	7' 8⅝"	7' 6¼"	71,650	5,071	66,579	1,172
			2,395					2,350	
	5,898	19' 4⅛"	7' 10¼"	2,393	7' 5¾"	2,280	30,480	2,300	28,180
71,196				5,071		62,126	1,165		

Hapag-Lloyd serial number excerpt	
HLBU 136800–139299	
HLXU 115000–132999	
HLXU 339700–346799	
CPSU 170000–183199	

8' 6" high	Inside dimensions			Door openings		Weights			Capacity
	Length	Width	Height	Width	Height	Max. gross	Tare	Max. payload	
	mm ft	mm ft	mm ft	mm ft	mm ft	kg lbs	kg lbs	kg lbs	m ³ ft ³
Steel floor Steel container with corrugated walls	5,900	2,352	2,393	2,340	2,292	32,500	2,250	30,250	33.2
	19' 4¼"	7' 8⅝"	7' 10¼"	7' 8⅝"	7' 6¼"	71,650	4,960	66,690	1,172
			2,395					2,570	
	5,666	7' 10¼"	2,300	7' 10¼"	5,071	66,579	5,071	30,200	66,579
5,666			65,984						

Hapag-Lloyd serial number excerpt	
HLBU 171950–173449	
HLBU 173450–174949	
HLXU 340700–340799	
HLBU 136800–139299	

For further information about the steel-floor container, please see page 32.