

HARDTOP CONTAINER

ISO Size Type Code: 22U6

20'



- This container type has been **designed and developed by Hapag-Lloyd**
- It has been specially constructed for
 - loading, e.g. by crane, through roof opening and door side
 - **heavy loads**
 - high and **excessively high loads**
- With the roof removed and the door header swung out, it is much easier to load cargo by forklift via the door side
- The steel roof is fitted with forklift rings so that it can be removed by using a forklift. The weight of the steel roof is approx. 450 kg (990 lbs)
- In case your cargo has an over-height, the roof sections can be lashed to a side wall inside the container using only approx. 13 cm (5' 1/8") of space
- Floor height 170 mm (ground level to interior floor surface, tolerance deviation possible)
- If required, we can provide disposable tarpaulins for transport that can be fastened to the walls on the outside using lashing devices
- Forklift pockets for loaded containers
- Can be used for bulk cargo
- Supplied with extra lashing rings/bars for transport of liner bags or hanging garment equipment
- The roof can be easily lifted by hand by 70 mm (2' 3/4"), using the roof-locking devices, so that the door header can be swung out without removing the roof
- Please bear in mind the prevalent weight restrictions for inland transport
- For dimensions of roof and door openings, please see page 22
- For further information, please see our brochure "The Hardtop Container"

8' 6" high	Inside dimensions				Weights			Capacity
	Length	Width	Height		Max. gross kg lbs	Tare kg lbs	Max. payload kg lbs	m ³ ft ³
			Middle mm ft	Side mm ft				
Wooden floor	5,895	2,350	2,384	2,309	32,500	2,850	29,650	32.1
Steel container with corrugated walls and removable steel roof	19' 4 ¹ / ₈ "	7' 8 ¹ / ₂ "	7' 9 ⁷ / ₈ "	7' 6 ⁷ / ₈ "	71,650	6,283	65,367	1,134
	5,886	2,342	2,388	2,313	30,480	2,700	27,780	33.0
	19' 3 ³ / ₄ "	7' 8 ¹ / ₈ "	7' 10"	7' 7"	67,196	5,952	61,244	1,165

Hapag-Lloyd serial number excerpt	
HLXU	365650-365949
HLXU	365000-365949
HLXU	365450-365649

Height middle can be used over a width of 2,000 mm (6'6")